



**ELECTRICAL PERFORMANCE:**

- 1. Impedance : 50 ohms
- 2. Frequency Range : 0~12.4 GHz
- 3. Working Voltage : 250 Vrms maximum
- 4. Dielectric Withstanding Voltage : 750 Vrms maximum
- 5. Insulator Resistance : 5000 Megohms minimum

4	HEAT SHRINK TUBE	P E	NONE
3	FERRULE	BRASS	GOLD
2	BODY CAP	BRASS	GOLD
1	SHELL	BRASS	GOLD
	GASKET	SI RUBBER	NONE
	"C" RING	BERYLLUM COPPER	NONE
	INSULATOR	TEFLON	NONE
	CONTACT	BRASS	GOLD 30U"
	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIALS	FINISHED

Recommended Stripping Cable Dim's

REV	DESCRIPTION	ECN	DRAWN	DATE
A	NEW RELEASE	01-271		09-05-2001

REVISIONS

REMARKS:

TOLERANCES:  
DIM: XX=±0.3  
UNIT: mm XXX=±0.15

TITLE: RP-SMA R/A PLUG CRIMP TYPE, FOR174/U CABLE

DESIGNED: 09-05-2001  
DRAWN: 09-05-2001  
CHECKED: APPROVAL

SHEET 1 OF 1  
SCALE: 5:1  
DWG NO: D600  
LAYER: ASY  
REV: A



P/No.: 19130822